


Trhací se zápuštnou hlavou

Al/St

dřík - hliník AlMg3,5
trn - ocel zinkovaná



d mm	vrtní mm	L mm	s mm	D mm	k mm	tah N	střih N
2,4	2,5	6,0	1,5-4,0	4,8	0,55	660	420
		8,0	4,0-6,0				
		10,0	6,0-8,0				
		12,0	8,0-10,0				
3,0	3,1	6,0	1,5-3,5	6,0	0,9	880	650
		8,0	3,5-5,5				
		10,0	5,0-7,0				
		12,0	7,0-9,0				
3,2	3,3	6,0	1,5-3,5	6,0	0,9	1000	740
		8,0	3,5-5,5				
		10,0	5,5-7,0				
		12,0	7,0-9,0				
4,0	4,1	6,0	1,5-3,0	7,5	1,0	1670	12100
		8,0	3,0-5,0				
		10,0	5,0-6,5				
		12,0	6,5-8,5				
		14,0	8,5-10,5				
		16,0	11,0-12,5				
		18,0	12,5-14,5				
20,0	15,0-16,5						
4,8	4,9	8,0	3,0-4,5	9,0	1,2	2940	2110
		10,0	4,5-6,0				
		12,0	6,0-8,0				
		14,0	8,0-10,0				
		16,0	8,0-12,0	9,0	1,2	2790	1870
		18,0	10,5-14,0				
		20,0	12,5-16,0				
		24,0	17,0-20,0				
27,0	20,0-23,0	9,0	1,2	2790	1870		
30,0	23,0-25,0	9,0	1,2	2790	1870		
5,0	5,1	6,0	3,0-4,0	9,0	1,2	2940	2110
		8,0	3,0-4,5				
		10,0	4,5-6,0				
		12,0	6,0-8,0				
		14,0	8,0-10,0				
		16,0	8,5-12,0				
		18,0	12,0-14,0				
		20,0	12,5-16,0				
		25,0	16,0-20,0				
		30,0	21,0-25,0				